



MATERIALS:

Flange and Support Arm – 18-8-S, type 304, 22 gauge (0.8mm) stainless steel. Concealed, 19 gauge (1.1mm) stainless steel mounting bracket. All- welded construction. Secured to wall plate with a stainless steel setscrew. Each hook holds 75kg downward pull when properly installed.

Concealed Wall Plate – 18-8 S type-304, 19 gauge (1.1mm) stainless steel

Hook – 18-8 S, type 304, 13 gauge (2mm) stainless Steel. Welded to the support arm.

INSTALLATION:

Mount Unit on wall. Firstly remove hooks from the compact strip.

To remove concealed wall plate from back of flange and mounting bracket, loosen setscrew. Mark on the compact strip, the centre of where each hook mounting bracket is placed and drill through the compact strip to the plaster wall or other dry wall construction. Provide fibre plugs or expansion shields for use with metal screws, or provide 3mm toggle bolts or expansion bolts. Secure Compact Strip to wall.

Once the compact strip is securely fixed to the wall construction (as per above), then re install the hooks to the compact strip concealing all the above wall fixings.

Re-installing hooks.

Mount wall plate so prongs are at top; secure with two sheet metal screws furnished by manufacturer, at points indicated by an S. Engage mounting bracket onto prongs of wall plate, then secure into position by tightening setscrew at bottom of flange.

SPECIFICATION:

Hook Strip shall be 13mm thick Compact Laminate. Width 100mm. Length nominal. Colour white or as per Architectural Specification. Surface mounted hat and coat hook shall be Bobrick B7682 (bright finish) or B76827 (satin finish) placed at 450mm centres.

Note: Custom Hook Strips are available using alternative style hooks according to the designers requirements.



RYNAT INDUSTRIES AUSTRALIA PTY LTD | www.rynat.com | Email: sales@rynat.com |

Aust Wide: 1300 558 518 | Tel: +61 8 6254 6555 | 20 Murray Rd South Welshpool WA |